Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

1 Identification · Product identifier Trade name: Jowatherm Reaktant 608.00 · Application of the substance / the mixture Adhesives · Uses advised against Restricted to professional users. · Details of the supplier of the safety data sheet Manufacturer/Supplier: Jowat SE Ernst-Hilker-Str. 10 - 14; D - 32758 Detmold Tel. +49 (0)5231 749 0; Fax +49 (0)5231 749 236 e-mail: info@jowat.de www.jowat.de Department issuing SDS: Environmental management Ellen Lange / Tina Friedrich / Jan-Peter Boelcke Fon +49 5231 749 218 / 270 / 211 e-mail: umweltmanagement@jowat.de Information provided by department: Jowat Corporation 5608 Uwharrie Rd. Archdale, NC 27263 P.O.Box 1368 High Point, NC 27261 Tel.: +1 336 434-9000 +1 336 434-9019 Fax: E-Mail: info@jowat.com · Emergency telephone number: 1 800 424 9300 (Chemtrec 24 hours service)

2 Hazard(s) identification

Classification of the substance or mixture

GHS08

GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: diphenylmethane diisocyanate

Hazard statements

H332 Harmful if inhaled.

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system

NFPA ratings (scale 0-4)



· HMIS ratings (scale 0-4)

HEALTH *1	Health = *1
FIRE 1	Flammability = 1
REACTIVITY 0	Reactivity = 0

Other hazards

- · Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- **Description:**
- Adhesive.

Polyurethane resin

Dangerous components:

CAS: 5873-54-1 diphenylmethane diisocyanate RTECS: NQ 9350000

1 - <5%

· Additional information

In case any risk phrases are listed, please refer to paragraph 16 for the exact wording.

4 First-aid measures

Description of first aid measures

· After inhalation

Supply fresh air and call in physician to be on the safe side. In case of unconsciousness place patient in stable side position for transportation. Supply fresh air; consult physician in case of problems.

After skin contact

After contact with the molten product, cool rapidly with cold water.

Do not peel solidified product from the skin.

- Seek medical treatment.
- · After eye contact Rinse opened eye for several minutes under running water.
- After swallowing If symptoms persist consult physician.
- · Information for physician
- Most important symptoms and effects, both acute and delayed Asthma attacks
 - Allergic reactions

Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

· Indication of any immediate medical attention and special treatment needed

(Contd. of page 2)

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol-resistant foam. Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

Hydrogen cyanide (HCN)

Advice for firefighters

Protective equipment: Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective clothing.

- · Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Pick up mechanically.

Allow to solidify. Pick up mechanically.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
629-11-8	hexane-1,6-diol	30 mg/m3
91-20-3	naphthalene	15 ppm
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m3
· PAC-2:		
629-11-8	hexane-1,6-diol	610 mg/m3
91-20-3	naphthalene	83 ppm
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m3
· PAC-3:		
629-11-8	hexane-1,6-diol	730 mg/m3
91-20-3	naphthalene	500 ppm
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m3

7 Handling and storage

· Handling

Precautions for safe handling

Store in cool, dry place in tightly closed containers.

Prevent formation of dust.

Ensure that suitable extractors/ventilation systems are available on processing machines and in the workplace. In the context of the risk assessment, it is necessary to evaluate whether and to what extent protective measures are required. If necessary, a workplace measurement has to be carried out. • Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

Storage

- Requirements to be met by storage facilities and containers: No special requirements.
- · Information concerning mixed product storage facilities: Not required.

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

· Further information on storage conditions:

Store in dry conditions.

Protect from humidity and water.

• Storage class 11

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring in the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

CAS No. Designation of material % Type Value Unit

Auditional Occupational Exposure Linnit Values for Dossible nazarus uurinu Drocessinu.	 Additional Occupational Ex 	posure Limit Values for	r possible hazards during p	rocessina:
--	--	-------------------------	-----------------------------	------------

101-68-8 4,4'-methylenediphenyl diisocyanate

- PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm REL Long-term value: 0.05 mg/m³, 0.005 ppm
- Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min
- TLV Long-term value: 0.051 mg/m³, 0.005 ppm

Additional information:

The lists that were valid at the date of compilation of this SDS were used as basis.

Exposure controls

Personal protective equipment

General protection and hygiene precautions
 The standard precautionary measures for handling chemicals should be observed.
 Keep away from food, beverages and animal feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Vacuum clean contaminated clothing. Do not blow or brush off contamination.
 Avoid skin contact with the liquefied material.
 Do not eat or drink while working.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation. Filter A/B/P2.

- · Protection of hands:
- Heat-resistant gloves
- Impervious aloves

Material of gloves

- Leather gloves
- Strong gloves

· Penetration time of glove material No special requirements.

• Eye protection: Not required.

9 Physical and chemical properties		
 Information on basic physical and c General Information Appearance: 	hemical properties	
· Form:	Solid.	
· Color:	According to product specification	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
Change in condition		
 Melting point/Melting range: 	undetermined	

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

	(Contd. of page 4	
 Boiling point/Boiling range: 	undetermined	
· Flash point:	>200 °C (>392 °F)	
· Flammability (solid, gaseous)	Not determined.	
· Ignition temperature:	>450 °C (>842 °F)	
· Decomposition temperature:	> 220 °C	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: · Lower: · Upper:	Not determined. Not determined.	
· Vapor pressure:	Not applicable.	
 Density: Relative density Vapor density Evaporation rate 	Not determined Not determined. Not applicable. Not applicable.	
Solubility in / Miscibility with Water:		
· Partition coefficient (n-octanol/water): Not determined.		
Viscosity: dynamic: kinematic:	Not applicable. Not applicable.	
• Solvent content: • Organic solvents:	0.0 %	
Solid content: Other information N VOC - Volatile Organic Compounds	100.0 % o further relevant information available.	
European Union Switzerland U.S.A (less water and less exempts)	0.00 % 0.00 % 0.0 g/l / 0.00 lb/gl	

10 Stability and reactivity

• Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.
- To avoid thermal decomposition do not overheat.
- Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point Reacts with water

- Reacts with humid air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:
- Nitrogen oxides
- Hydrogen cyanide (prussic acid)
- Isocyanate
- Flammable gases/vapors
- Carbon monoxide and carbon dioxide
- Danger of toxic pyrolysis products

Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

Nitrogen oxides (NOx)

(Contd. of page 5)

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

	 LD/LC50 values that are relevant for classification: 		
	Inhalative	LC50 / 4 h	12 mg/l (rat)
5873-54-1 diphenylmethane diisocyanate			
	Oral	I D50 oral	2000 mg/kg (rat)

Oral	LD50 oral	2000 mg/kg (rat)
		9400 mg/kg (rabbit) (OECD 404)
Inhalative	LC50 / 4 h	0.31 mg/l (rat)

Primary irritant effect:

• on the skin: No irritant effect.

· on the eye: No irritating effect.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations (Directive 1999/45/EC of the European Parliament and of the Council) as issued in the latest version: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.
· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.
12 Feelenieel information

12 Ecological information

· Toxicity

· Aquatic to	xicity:	
5873-54-1 diphenylmethane diisocyanate		
LC50 / 96 h	> 1000 mg/l (zebrafish)	
LC0	> 1000 mg/l (zebrafish)	
EC50 / 24 h	> 1000 mg/l (water flea) (OECD 202)	
EC50 / 3 h	> 100 mg/l (activated sludge) (OECD 209)	
EC50 / 72 h	> 1640 mg/l (scenedesmus subspicatus) (OECD 201)	
	and degradability No further relevant information available.	

Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
 - · General remarks:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Prevent undiluted product or product in large amounts to reach ground water, open waters or sewer systems.

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

(Contd. of page 6)

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

· Recommendation Smaller quantities can be disposed of with household waste.

• Uncleaned containers/packaging materials: • Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

· UN-Number · DOT, ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Void	
 Packing group DOT, ADR, IMDG, IATA 	Void	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	Il of Not applicable.	
· UN "Model Regulation":	Void	

¹⁵ Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Section 355 (extremely hazardous substances)
None of the ingredients is listed.

• SARA Section 313 (specific toxic chemical listings)

5873-54-1 diphenylmethane diisocyanate

• TSCA (Toxic Substances Control Act) (Substances not listed)

All ingredients are listed.

Proposition 65

Prop 65 - Chemicals known to cause cancer

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity

None of the ingredients is listed.

Cancerogenity categories

• EPA (Environmental Protection Agency)

None of the ingredients is listed.

Printing date 03/02/2017

Version number 4

Reviewed on 03/02/2017

Trade name: Jowatherm Reaktant 608.00

(Contd. of page 7)

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present state of information. They shall, however, not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. All standard industrial precautions apply, concerning protection of health, and safe handling. The recommendations have to be examined in the context of the application for which the product is intended, and observed as necessary.

· Date of preparation / last revision 03/02/2017 / 3

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Acute Tox. 4: Acute toxicity - Category 4 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data in paragraphs with asterisk are revised in comparison to the previous version.